



Made in South Africa

Walcro®

Urinal Flushing Valves

WALCRO Exposed Urinal Flushing Valves

WALCRO 330UR Urinal Flushvalve

Inlet: Ø 15mm BSP, Female
Maintained pressure:
100kPa to 600kPa.
Installation: Exposed chrome,
single bowl urinals only.
Not suitable for siphonic urinal bowls.
Made in S.A. from DZR Brass,



WALCRO Exposed Urinal Flushing Valves

WALCRO 103LUR Urinal Flushing Valve

Inlet: Ø 20mm BSP, Female
Maintained pressure:
30kPa to 600kPa.
Installation: Exposed, chrome,
SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO Built-in Urinal Flushing Valves

WALCRO 150BUR Urinal Flushing Valve

Inlet: Ø 15mm BSP, Female
Maintained pressure:
30kPa to 600kPa.
Installation: Built-in valve for
single bowl urinal. Requires a
back entry bowl.
Made in S.A. from DZR Brass,



WALCRO Built-in Urinal Flushing Valves

WALCRO 150URS Urinal Flushing Valve

Inlet: Ø 15mm BSP, Female
Maintained pressure:
30kPa to 600kPa.
Application: Prison & high
vandalism projects
Installation: Built-in valve with
special sleeve for single bowl
urinals.
SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO Concealed Valve

WALCRO 103LURC Urinal Flush Valve

Inlet: Ø 20mm BSP, Female
Maintained pressure:
30kPa to 600kPa
Installation: Concealed duct
SABS, Jaswic, DZR Brass,
made in S.A.



WALCRO High volume valve

WALCRO 550 Exposed Urinal Flush Valve

Inlet: Ø 20mm BSP, Female
Maintained pressure:
100kPa to 600kPa.
Note: This is a toilet flushing valve to
provide more water.
Application: High volume applications
such as S.S.trough & multiple stall
flushing. Too big for single bowl urinals.
Installation: Exposed,
SABS, Jaswic, DZR Brass, made in S.A.



WALCRO Flush Pipes

**WALCRO
S/WAL 15TP
Urinal Pipe**
Ø 15mm (1/2")
offset flush
pipe for the new
**Walcro 330UR
Valve and
Walcro 103LUR
Valve**



**WALCRO
103/6
Urinal Pipe**
Ø 15mm (1/2")
straight urinal
flush pipe with
spreader



Special

Siphonic Urinals-NB

Siphonic type urinal bowls require a higher volume
of water to flush effectively.

Please contact us for valve selection.

In some cases we use the 550 toilet valve on a
siphonic urinal to give more water

Walker Croswell

Walker Croswell (Pty) Ltd PO Box 1018, Bromhof, 2154.
Walcro House, Bush Hill Office Park, Rachele Close,
Ostrich Road (corner Hawken), Bromhof,
Randburg, Gauteng, South Africa
Telephone: 011 793-1031 Fax: 011 793-1092
Cape Town: 021 797-4327 or Cell: 072 821 4463
e-mail: walcro@jafica.com Website: www.walcro.co.za